

APPENDIX A.1
Pricing for TXShare Cooperative Purchase Program Participants

Item	Description	Unit of Measure	% Discount off Current List Unit Price at Plant Pickup in Dallas/Fort Worth	Location of Plant Sites for Pickup for Dallas/Fort Worth Customers	% Discount off Current Truck Delivery Rate per Mile to Location in DFW	Alternate Plant Site Location(s) for Pickup for Customers outside Dallas/Fort Worth	% Discount off Current Truck Delivery Rate per Mile to Location outside DFW	Minimum Order for Pickup at Plant	Minimum Order for Delivery													
23	Flexible Base Material - Type C Spec - Type C, Crushed Gravel, meets or exceeds TXDOT Item 247.																					
24	Flexible Base Material - Type D Spec - Type D, Crushed Concrete, meets or exceeds TXDOT Item 247.	TON	Ø	1. See Attached																		
24A	Flexible Base Material - Type D Fine Spec - Type D, Crushed Concrete, Fine, meet or exceed TXDOT Item 247. Per the following screening size: <table border="1" style="margin-left: 20px;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing by Weight</th> </tr> </thead> <tbody> <tr> <td>3/8 in. (9.5 mm)</td> <td>100</td> </tr> <tr> <td>No. 4 (4.75 mm)</td> <td>95 - 100</td> </tr> <tr> <td>No. 16 (1.18 mm)</td> <td>50 - 90</td> </tr> <tr> <td>No. 50 (300 µm)</td> <td>5 - 30</td> </tr> <tr> <td>No. 100 (150 µm)</td> <td>0 - 10</td> </tr> <tr> <td>No. 200 (75 µm)</td> <td>0 - 3</td> </tr> </tbody> </table>	Sieve Size	Percent Passing by Weight	3/8 in. (9.5 mm)	100	No. 4 (4.75 mm)	95 - 100	No. 16 (1.18 mm)	50 - 90	No. 50 (300 µm)	5 - 30	No. 100 (150 µm)	0 - 10	No. 200 (75 µm)	0 - 3							
Sieve Size	Percent Passing by Weight																					
3/8 in. (9.5 mm)	100																					
No. 4 (4.75 mm)	95 - 100																					
No. 16 (1.18 mm)	50 - 90																					
No. 50 (300 µm)	5 - 30																					
No. 100 (150 µm)	0 - 10																					
No. 200 (75 µm)	0 - 3																					
25	Flexible Base Material - Type E Spec - Type E, Caliche, meet or exceed TXDOT Item 247.																					
26	Surface Treatment Aggregate, Type D, Grade 3 Spec - Meets or exceeds TXDOT Item 302, (Aggregates for Seal Coats).																					
27	Surface Treatment Aggregate, Type D, Grade 4 Spec - Meets or exceeds TXDOT Item 302, (Aggregates for Seal Coats).																					
28	Three-Quarter-Inch Washed Rock Spec - Road Rock – Crushed Limestone rock. Size of rock that will pass 3/4" and be retained on next smaller size screen.																					
29	Fill Material Spec - Fill material shall be suitable material containing no muck, quicksand, organic matter or other material that will prevent the solid formation of a suitable and enduring roadbed or embankment structure.																					

Item	Description	Unit of Measure	% Discount off Current List Unit Price at Plant Pickup in Dallas/Fort Worth	Location of Plant Sites for Pickup for Dallas/Fort Worth Customers	% Discount off Current Truck Delivery Rate per Mile to Location in DFW	Alternate Plant Site Location(s) for Pickup for Customers outside Dallas/Fort Worth	% Discount off Current Truck Delivery Rate per Mile to Location outside DFW	Minimum Order for Pickup at Plant	Minimum Order for Delivery
30	Topsoil Spec - Topsoil shall consist of a uniform mixture of 50% sand and 50% muck in a loose friable condition. Topsoil shall be free of sticks, stones, and other objectionable material.								
31	Top Dressing Lawn Sand Spec - One hundred (100%) percent Lawn Sand – number thirty (30) sieve size (sixty-nine (69%) percent, passing thru or not more than thirty (30%) retained) of which ninety-eight (98%) percent is pure silica.								

Category 2: Asphalt Materials

Item	Description	Unit of Measure	% Discount off Current List Unit Price at Plant Pickup in Dallas/Fort Worth	Plant Site Location for Pickup for Dallas/Fort Worth Customers	% Discount off Current Truck Delivery Rate per Mile to Location in DFW	Alternate Plant Site Location(s) for Pickup for Customers outside Dallas/Fort Worth	% Discount off Current Truck Delivery Rate per Mile to Location outside DFW	Minimum Order for Pickup at Plant	Minimum Order for Delivery	Upcharge for Demurrage Rate if Applicable
32	Limestone Rock Asphalt Spec - Meets or exceeds TXDOT specification DMS-9210.									
33	Rapid Curing Asphaltic Concrete Patching Material (Container). Spec - Meets or exceeds TXDOT Spec DMA-9203 for concrete mixture intended on roadways that demand high early mixture stability.									
34	Asphaltic Patching Material (Stockpile Storage or Bagged). Spec - Meets or exceeds TXDOT Spec DMS-9202 - crushed stone asphaltic concrete intended primarily as a cool-to cold-weather stockpile or bagged patching mix for maintenance.	TON		see Attached						
35	Cold Patch Oil Sand Spec- 90% sand, 10% 3/8" clean aggregate and 6% Asphalt Cement meets or exceeds TxDOT Item 300 specification for AC 0.6 or AC 1.5. This is a pothole patching material and can be used to blade on the roadway. Mixing plant capable of drying the material before applying the liquid asphalt. Material should be workable in a stockpile for 6 months.									
36	Emulsified Asphalt. Spec - Provide emulsified asphalt that is homogeneous, does not separate after thorough mixing, and meets or exceeds the requirements for the specified type and grade in TXDOT Specification 300, Tables 7, 8, 9, and 10.									

Low-grade crushed Asphalt 1/2" - minus